

Specifications


SMART kapp 🚺

SMART kapp[™] 42" capture board (kapp42)

Overview


The SMART kapp[™] 42" capture board enables you to collaborate with others in a simple but powerful way. Write and draw on the capture board like you would a regular dry erase board. You can then connect a Bluetooth[®]-enabled mobile device to the capture board by scanning a Quick Response (QR) code or by tapping the Near Field Communication (NFC) target. When you first connect your mobile device, you're directed to the Apple App Store or Google Play[™] to download the SMART kapp app. After you download and install the app, you can use it to connect to your capture board and share content with others.

See smartkapp.com for more information on this product.



Dimensions and weights¹

Dimensions



Weight (approximate) 35 lb. (16 kg) Shipping dimensions (approximate) 48" × 26" × 8" (122 cm × 66 cm × 20.3 cm) Shipping weight (approximate) 43 lb. (19.5 kg)

¹All dimensions \pm 1/8" (0.3 cm). All weights \pm 2 lb. (0.9 kg).

SPECIFICATIONS SMART KAPP 42" CAPTURE BOARD (KAPP42)

Parts and features

Included parts	SMART kapp 42" capture board Dry-erase marker (×3) Eraser Bracket and hardware for mounting the capture board to a wall
Digital capture technology	DViT® (Digital Vision Touch) technology
Wireless technology	Bluetooth 2.1 + EDR ²
Capture options	 Establish a Bluetooth wireless connection with a supported mobile device (see below) by doing one of the following: Scan the capture board's unique QR code Tap the capture board's NFC target (Android[™] devices only) Connect a USB drive
USB drive support	USB 2.0 Type-A receptacle Support for FAT-formatted USB drives only

Mobile device support

Apple devices	iOS 7 or later operating system software 50 MB storage iPhone 4S or later Third generation iPad or later First generation iPad mini or later
Android devices	 Android 4.1 (Jelly Bean) or later operating system 50 MB of storage (internal or SD card) Devices meeting the following specifications: 1024 MB of RAM 720p or better screen resolution Bluetooth 2.1 + EDR NFC reader (recommended) 3 megapixel or better rear-facing camera (recommended)
Mounting	
Options	Included mounting bracket Standard VESA® 400 mm × 400 mm mounting bracket
Recommended height	69" (175.3 cm) from the floor to the middle of the included mounting bracket

 $^2 \mbox{Compatible}$ with Bluetooth 3.0 and dual-mode Bluetooth 4.0

Power

Power specifications	5V, 3A
Power cable	9' 10" (3 m) power cable

Storage and operating requirements

Storage

Temperature	-40–140°F (-40–60°C)
Humidity	5–95% relative humidity, non-condensing
Operating	
Temperature	41–95°F (5–35°C)
Humidity	10–80% relative humidity, non-condensing

Certification and compliance

Regulatory certification	CE, ETL, C-Tick, FCC
Environmental compliance	
European Union	REACH, RoHS, WEEE and Packaging
U.S.	Packaging and Conflict Minerals
European Union	REACH, RoHS, WEEE and Packaging

Purchasing information

Order numbers	
1024494	SMART kapp 42" capture board (kapp42)
Warranty	One-year limited equipment warranty
Replacement parts	Replacement pens and erasers can be purchased from the Store for SMART Parts (see smarttech.com/Support/PartsStore)

smarttech.com/support

smarttech.com/contactsupport

© 2014 SMART Technologies ULC. All rights reserved. SMART kapp, DViT, smarttech, the SMART logo and all SMART taglines are trademarks or registered trademarks of SMART Technologies ULC in the U.S. and/or other countries. Apple, iPhone and iPad are trademarks of Apple Inc., registered in the U.S. and other countries. Android and Google Play are trademarks of Google Inc. The Bluetooth word mark is owned by the Bluetooth SIG, Inc. and any use of such marks by SMART Technologies ULC is under license. All other third-party product and company names may be trademarks of their respective owners. This product and/or use thereof covered by one or more of the following U.S. patents. www.smarttech.com/patents. Contents are subject to change without notice. 05/2014.